



SER-HİDROLİK KAFALI ŞİŞİRME MAKİNALARI / SER-HYD.HEAD BLOW MOULDING MACHINES					
TEKNİK DEĞERLER / TECHNICAL DATA	BİRİM UNIT	MAKİNA TİPİ / MACHINE TYPE			
		Ø90 20-30 Lt	Ø100 60 Lt	Ø110 120 Lt	Ø130 220 Lt
VİDA ÇAPI / SCREW DIAMETER	mm	90	100	110	130
MAX. VİDA DEVRİ / MAX. SCREW R.P.M	Rev/Min	65	65	65	65
MAL HAZNESİ / PLAS. AKU. CAPACITY	cm ³	4.000	7.000	10.000	15.000
EXT. MOTORU / EXT. MOTOR POWER	kW	37	45	55	75
EXT. VERİMİ / EXT. OUTPUT	kg/h	150	180	220	280
HİDROLİK POMPA / HYDRAULIC PUMP	Lt	113+77	136+77	136+95	136+95
HİD. MOTOR GÜCÜ / HYD. MOTOR POWER	kW	22	30	30	30
MENG. KAPAMA GÜCÜ / CLAMP. FORCE	Ton	20	30	40	55
PLAKA ÖLÇÜLERİ / PLATE DIMENSIONS	mm	600x900	700x1100	850x1250	1200x1450
KALIP ARALIĞI / CLAMPING DISTANCE	mm	200x1100	300x1300	350x1400	400x1700
ISITMA BÖLGESİ / HEATER ZONE	Ad/Pcs	4+5	4+5	4+5	4+5
ISITMA GÜCÜ / HEATER CAPACITY	kW	22	30	35	40
TOPLAM GÜÇ / TOTAL POWER CAPACITY	kW	81	105	120	145
MAKİNA AĞIRLIĞI / MACHINE WEIGHT	Ton	14	16	20	25
HAVA TÜKETİMİ / USING COMP. AIR	Lt/Min	300	500	750	1000
SU TÜKETİMİ / USING COOLING WATER	Lt/Min	150	200	250	300
MAKİNA ÖLÇÜLERİ (B x E x Y) MACHINE DIMENSIONS (L x W x H)	mm	3500 5500 3750	3750 6000 3900	4000 6250 4000	4250 6500 4250